


# Goldeneye 900

Transverse Quality Scanner for rip, trim, grading & sorting solutions



## Goldeneye 900

- × The No.1 transverse scanner with optional X-ray
- × Four sided scanning in one pass
- × Modular design
- × Scans planed & rough lumber
- × For green, dry & planer mills

# Next generation transverse lumber scanning

The world's No.1 Multi-Sensor Quality Scanner in transverse transport with optional X-ray, the Goldeneye 900, is a showcase of the innovative technological capabilities of Microtec.

Goldeneye 900 determines the overall quality of green, dry or planed lumber in one pass from all four sides.

Value optimization before and after kiln drying is possible as the Goldeneye 900 grades both rough and planed lumber.

The scanner detects and localizes all types of knots as well as cracks, discoloration, pitch pockets, waness, curvature, and other dimensional defects. This allows customers to automate, streamline and optimize all further production steps.

## Production Applications


### Sawmill

- × Rip/Edger
- × Sorting
- × Trimming

### Planermill

- × Sorting/Cross-cutting
- × Trimming
- × Structural
- × Glulam/CLT
- × NGR

Goldeneye 900 Multi-Sensor Transverse Quality Scanner reliably identifies wood defects, grading both planed as well as rough lumber as four-sided or two-sided scanner.



## Goldeneye 900 Multi-Sensor Transverse Quality Scanner features

- × Transverse transport
- × One scan solution from all 4 sides
- × Optional full-length X-ray scanning
- × Simple installation, no elevation changes
- × Scans planed and rough lumber
- × Grades lumber based on individual quality parameters

## Full quality grading

Goldeneye 900 provides accurate 3D defect reconstruction as well as precision and reliability in determining the surface quality of green and dry boards in transverse feeding. The seamless integration of color and laser scanners into one multi-sensor system delivers a gapless view of the surface of lumber. The compact, single pass design ensures a fast and straightforward installation. Since the boards do not need to be turned, the scanner only requires a single scan frame width. As no elevation changes are required, the scanner can be placed in an existing grading station or transverse chain section with minimal modification. The optimization software enables individual management of real and virtual optimization parameters for peak recovery. The evaluation of the scanned information is done using Microtec's powerful image processing and optimization algorithms to maximize recovery of downstream production processes.

- × Accurately recognizes, localizes and sizes knots and other defects such as cracks, pitch pockets, and discoloration
- × Modular design, depending on the board length
- × Implements customer specific grading, trimming and sorting rules
- × Comprehensive and easy to use user interface



Goldeneye 900 features Multi-Sensor cameras and sensors for laser scattering, laser 3D triangulation, color analysis and X-ray scanning.

## Goldeneye 900

	901	902	906
Dimension (3D laser triangulation)	✓	✓	✓
Grain deviation (laser scatter)	✓	✓	✓
Color	✓	✓	✓
X-ray		✓	✓
Resonance frequency (laser interferometer)			✓
Board cross-section	up to 130 x 900 mm (5 x 26 in), depending on lug space		
Conveyor speed	up to 200 lugs/min		



# World leading wood scanning solutions



Microtec  
Via Julius-Durst Straße 98  
39042 Bressanone/Brixen, Italy  
T + 39 0472 273 611  
[info@microtec.eu](mailto:info@microtec.eu)  
[microtec.eu](http://microtec.eu)

The information contained in this catalog may be  
subject to technical changes and modifications.  
Design: [www.farbfabrik.it](http://www.farbfabrik.it)  
© Microtec. All rights reserved. 05/2019

